

## Air condition (HVAC) :: Ventilation ducts ::

Disinfection module as barrier for air conditioning or ventilation systems



- Continuous disinfection by up to 99 %
- No chemical disinfection necessary
- Simple installation by a HVAC engineer
- Compliance vorgegebener Hygiene-standards





## Fields of application:

Built into the air ducts of ventilation and air conditioning systems (AHU/HVAC), the modules prevent the multiplying of dangerous viruses, bacteria, mold and spores and their distribution.

A perfect solution for large ducts with high air flows.

The installation is carried out in such a way that the air flow hits the UV lamps vertically and therefore receives the highest possible dose of UVC radiation.

The modules consist of batteries with 4 or 6 lamps, built in a sturdy stainless steel frame. The different lengths and widths of the modules allow the use in almost all duct dimensions, since the cross-flow allows them to be mounted side by side or as a labyrinth. Each module has a control box with optical monitoring of the individual emitters.

## Features:

- Selectable UV-C lamp power
- Stainless steel frame AISI 304
- Various sizes available
- All components are UV-C stable
- Including external control box
- Control via cable/plug connector
- CE sign (LVD, EMC, MD, RoHS)

UV-DUCT-SQ	4/40H	4/90H	4/120H	6/40H	6/90H	6/120H
Item No.	A005893	A005894	A005895	A005896	A005897	A005898
Power consumption (W)	160	320	400	240	480	600
Voltage (V)	230	230	230	230	230	230
Protection class	IP55	IP55	IP55	IP55	IP55	IP55
Length cable (m)	3	3	3	3	3	3
Dimensions (LxWxH,	90x450	90x450	90x450	90x600	90x600	90x600
mm)	x496	x953	X1,234	x496	x953	X1,234
Lamp lifetime (h)	9,000	9,000	9,000	9,000	9,000	9,000
Alarm card/ Item No.	2 X	Included in	Included in	3 X	Included in	Included in
Alailii Caru, item No.	AL-2X	EPS	EPS	AL-2X	EPS	EPS
Spare lamp/ Item No.	A003389	A003926	A007961	A003389	A003926	A007961