

## TS 200-1200

### Immersion emitter with single switch box

The TS immersion emitter system is designed to effectively sterilize water in air washers, cooling towers, fountains, tanks, humidification systems or ponds. These UV-C emitters expose the water to a high dose of UV-C, killing unwanted microorganisms and preventing algae growth.

**Applications:** Air washers | Cooling towers | Fountains | Humidifiers | Filter systems (fish farming) | Algae prevention in pond filters | Water tanks | OEM machine and system construction | Breweries



**Function:** The immersion emitters are placed directly in systems/water basins using a stainless steel plate or attached directly to the container

**Equipment:** Amalgam high-power emitters; completely waterproof unit – protective class IP68; contains power unit with integrated ballast electronics

**Assembly/maintenance:** Turnkey ready; attached directly to the container or inserted in the basin/system with the use of a stainless steel plate

**Option:** 6m/10m connection cable extension

### Technical Data

Type	TL & TS 200	TL & TS 300	TL & TS 400	TL & TS 500	TL & TS 600
Dimension in mm	D30 × L250	D30 × L350	D30 × L450	D30 × L450	D30 × L650
Housing material	V4A stainless steel				
Emitter ST1	1x UV-C high efficiency / 12.000 h				
Power with Hg in W	7	13	18	23	29
Power with Amalgam in W			55		
Voltage	230V ± 10% (50 – 60Hz)				
Connection cable in m	3 / 6 / 10	3 / 6 / 10	3 / 6 / 10	3 / 6 / 10	3 / 6 / 10
Weight in kg	0.47	0.5	0.54	0.57	0.58
TS single switch box weight (kg)	1.95	1.95	1.95	1.95	1.95
Protection class	waterproof				

Continued on Page 2.

Type	TL & TS 700	TL & TS 810	TL & TS 1000	TL & TS 1200
Dimension in mm	D30 × L750	D30 × L860	D30 × L1050	D30 × L1250
Housing material	V4A stainless steel			
Emitter ST1	1x UV-C high efficiency / 12.000 h			
Power with Hg in W	35	40	50	61
Power with Amalgam in W		110		
Voltage	230V ± 10% (50 – 60Hz)			
Connection cable in m	3 / 6 / 10	3 / 6 / 10	3 / 6 / 10	3 / 6 / 10
Weight in kg	0,62	0,62	0.73	0.78
TS single switch box weight (kg)	1.95	1.95	1.95	1.95
Protection class	waterproof			